

Tire size	Operating code				EU tire label			Rim		Tire dimensions						Tire fitment		Load capacity (kg) per axle at inflation pressure <sup>6)</sup> (bar) (psi)																
	Pattern	LI/SI <sup>1)</sup>	PR	Speed index and ref. speed (km/h)	TT/TL <sup>2)</sup>	T <sup>3)</sup>	E <sup>4)</sup>	S <sup>5)</sup>	Rim-width	Min. distance between rim centers	Max. standard value in service		Design value		Stat. radius	Rolling circumference	LI <sup>1)</sup>	Tire fitment																
											Width	Outer-Ø	Width + 1 %	Outer-Ø ± 1 %					± 1.5 %	± 2 %	4.5 (65)	5.0 (73)	5.5 (80)	6.0 (87)	6.5 (94)	7.0 (102)	7.5 (109)	8.0 (116)	8.5 (123)	9.0 (131)				
315/60 R 22.5	HD Hybrid ContiRe	152/148 L	20	L 120	TL	-	-	-	9.00 9.75	344 352	318 326	966		306 313	950	445	2879	154 152 150 148	S S D D	4305 4075 7695 7235	4685 4435 8370 7870	5055 4785 9035 8495	5420 5130 9685 9105	5780 5470 10325 9710	6130 5805 10955 10305	6480 6135 11580 10885	6825 6460 12195 11465	7160 6780 12800 12035	7500 7100 13400 12600					
	HSW 2 SCAN XL	154/150 L	20	L 120	TL	C	C	↻ 73																										
	HDW 2 SCAN	152/148 L	20	L 120	TL	D	C	↻ 75																										
	Conti Urban HA3 M+S	152/148 J (154/150 E)	16	J 100 (E 70)	TL	C	B	↻ 71																										
385/65 R 22.5	HSL 2+	160/- K (158/- L)	20	K 110 (L 120)	TL	C	B	↻ 70	11.75 12.25		405 410	1092		389 394	1072	496	3248	164 162 158	S S S	5740 5455 5110	6245 5935 5555	6740 6405 6000	7225 6865 6430	7705 7320 6855	8175 7765 7275	8640 8210 7690	9100 8645 8095	9550 9075 8500	10000 9500 9000					
	Conti EcoPlus HT3	160/- K (158/- L)	20	K 110 (L 120)	TL	A	C	↻ 69																										
	ContiRe EcoPlus HT3	160/- K (158/- L)	20	K 110 (L 120)	TL	-	-	-																										
	Conti Hybrid HS3	160/- K (158/- L)	20	K 110 (L 120)	TL	C	B	↻ 73																										
	HSR 2 XL	164/- K	20	K 110	TL	C	C	↻ 73																										
	HSR 2	160/- K (158/- L)	20	K 110 (L 120)	TL	C	C	↻ 73																										
	Conti Hybrid HT3	160/- K (158/- L)	20	K 110 (L 120)	TL	B	B	↻ 73																										
	HTR 2 XL	164/- K	20	K 110	TL	B	C	↻ 71																										
	HTR 2	160/- K (158/- L)	20	K 110 (L 120)	TL	C	C	↻ 73																										
	HTR 2 ED	160/- K (158/- L)	20	K 110 (L 120)	TL	B	C	↻ 71																										
	HTR 2 ContiRe	160/- K (158/- L)	20	K 110 (L 120)	TL	-	-	-																										
	HSW 2 SCAN	160/- K (158/- L)	20	K 110 (L 120)	TL	D	C	↻ 73																										
	HTW 2 SCAN	160/- K (158/- L)	20	K 110 (L 120)	TL	D	C	↻ 73																										

See flap inside back cover for footnotes